



TASK FORCE TIPS®
FIRE FIGHTING EQUIPMENT

www.tft.com
3701 Innovation Way
Valparaiso IN
46383-9327
800-348-2686

B-BGT

Task Force Tips © 2016

ULTIMATIC 125 WITH IMPULSE TRIGGER VALVE SYSTEM 1" NH (25mm)

Part No: **B-BGT**



Fog Pattern Method	Molded Rubber Teeth (fixed)
Flow Rate	10-125 gpm (40-500 l/min)
Coupling Size (Nozzles)	1.0 inch (25mm)
Coupling Style (Nozzles)	Knurled (Diamond pattern)
Coupling Swiveling/Rigid (Nozzles)	Swivel (full time, even after tightening)
Pressure	100 psi (7bar)
Nozzle Body Style	Nozzle with shutoff and pistol grip
Valve Design	Slide Valve (Stainless)
Valve Actuation Method	Valve w/Trigger
Nozzle Bumper Material	Rubber - bonded

Details

ULTIMATIC 125 WITH IMPULSE TRIGGER VALVE SYSTEM 1" NH (25mm)

Full automatic 100 psi (7 bar) nozzle for use on 3/4" (19mm) or 1" (25mm) hose. Flow range of 10-125 gpm (40-500 l/min). Includes pistol grip mounted below the valve, flush without shutting down, trigger operated slide valve, "Gasket Grabber" inlet screen, and molded rubber bumper with "power fog" teeth. Lightweight hardcoat anodized aluminum for maximum resistance to corrosion and wear. 1" NH (25mm) full-time swivel is standard.

Weight: 3.400 lbs (kg)

Task Force Tips ® is a registered trademark of Task Force Tips, Inc.
TFT ® is a registered trademark of Task Force Tips, Inc.