



XFC-32

Task Force Tips © 2013

SAFE-TAK COMBINATION PACKAGE

Part No: **XFC-32**



Monitor Configuration	Portable
Flow Rate - Monitors	0-1250 gpm (0-4500 l/min)
Operation Energy Source	Manual
Monitor Inlet	Quick Connect Female (XF)
Monitor Outlet	2.5 inch (65mm)
Horizontal Control	Lever Action Rotational Lock
Horizontal Movement (degrees)	270 degrees
Vertical Control	Handwheel (6 Inch, Injection Molded Nylon)
Vertical Movement (degrees)	90 below to 90 above horizontal
Finish	Powdercoated Fire Engine Red

Related Videos

- [Replacing the Rotation Lock on a Crossfire Monitor](#)
- [Crossfire Monitor Video](#)

Online Technical Support Material

- [XFC-32](#)
- [Crossfire Demo Sheet](#)
- [Crossfire Monitor Safe-Tak Valve Operating Test](#)
- [Monitor Workbook & Training Program](#)
- [Crossfire Truck Mount Adapter](#)
- [Crossfire SAFE-TAK Base Instruction Manual](#)
- [Crossfire with STOW-A-WAY 800 Base Manual](#)
- [Crossfire w/FoamJet CCCF Certification](#)

Details

SAFE-TAK COMBINATION PACKAGE
CROSSFIRE-BASE-MSTR

Weight: 52.200 lbs (23.677 kg)

PRODUCT SERIES OVERVIEW

- The Crossfire with its 1250gpm rated flow in fixed or portable operations, integrates the unique Safe-Tak valve to prevent unintentional movement during operations.
- The Crossfire includes a lightweight portable base with stainless spring steel folding legs with carbide tips to provide improved stability during operations on all surfaces. Also included as standard equipment is a quickly deployable safety tie down strap, rotational lock, and an easy to see attachment lock mechanism.
- The Crossfire is available with your choice of combination nozzles or stacked tips, incorporates an automatic drain feature, and easy to read pressure gauge, and offers an easily upgradeable inlet component.

CROSSFIRE® is a registered trademark of Task Force Tips, Inc.
Task Force Tips® is a registered trademark of Task Force Tips, Inc.
TFT® is a registered trademark of Task Force Tips, Inc.