



XFT-NJ

Task Force Tips © 2013

CROSSFIRE MONITOR TOP 2.5"NH (65mm) OUTLET

Part No: **XFT-NJ**



Monitor Configuration	Portable
Flow Rate - Monitors	0-1250 gpm (0-4500 l/min)
Operation Energy Source	Manual
Monitor Inlet	Quick Connect Female (XF)
Monitor Outlet	2.5 inch (65mm)
Coupling Size Side A	2.5 inch (65mm)
Coupling Style Side A	Rocker
Horizontal Control	Lever Action Rotational Lock
Horizontal Movement (degrees)	Continuous 360
Vertical Control	Handwheel (6 Inch, Injection Molded Nylon)
Vertical Movement (degrees)	90 below to 90 above horizontal
Safety Shutoff	No Safety Shutoff
Pressure Relief Valve	No PRV
Valve Design	No Valve
Finish	Powdercoated Fire Engine Red
Certifications	N/A

Details

CROSSFIRE MONITOR TOP 2.5"NH (65mm) OUTLET can be connected to either a portable base or a truck with the adapters on page 70 or a TFT Extend-A-Gun with XL outlet on page 135. The connection is easy, positive, and visually verified. When in use, the release is "locked out" by water pressure. The waterway is a large 3.25" (83mm) which lets the CROSSFIRE deliver up to 1250 gpm (4500 l/min) with low friction loss. Horizontal rotation is securely locked with a simple lever, and position can be visually confirmed. Only seven (7) turns of the handwheel change the discharge elbow from vertical to the stop elevation. Includes highly visible pressure gauge and built-in automatic drain valve. Standard outlet thread is male 2.5" NH (65mm).

Weight: 17.000 lbs (7.711 kg)

Related Videos

- [Replacing the Rotation Lock on a Crossfire Monitor](#)
- [Crossfire Monitor Video](#)

Online Technical Support Material

- [XF500-Kit & XP500-Kit Installation Instructions](#)
- [XFT-NJ](#)
- [Really Campaign - Crossfire Portable Monitor](#)
- [Crossfire Demo Sheet](#)
- [Crossfire Monitor Safe-Tak Valve Operating Test](#)
- [Monitor Workbook & Training Program](#)
- [Crossfire Truck Mount Adapter](#)
- [Crossfire SAFE-TAK Base Instruction Manual](#)
- [Crossfire with STOW-A-WAY 800 Base Manual](#)
- [Crossfire w/FoamJet CCCF Certification](#)

PRODUCT SERIES OVERVIEW

- The Crossfire with its 1250gpm rated flow in fixed or portable operations, integrates the unique Safe-Tak valve to prevent unintentional movement during operations.
- The Crossfire includes a lightweight portable base with stainless spring steel folding legs with carbide tips to provide improved stability during operations on all surfaces. Also included as standard equipment is a quickly deployable safety tie down strap, rotational lock, and an easy to see attachment lock mechanism.
- The Crossfire is available with your choice of combination nozzles or stacked tips, incorporates an automatic drain feature, and easy to read pressure gauge, and offers an easily upgradeable inlet component.