



Y4-M11A

Task Force Tips © 2013

Manually Controlled Monitor - Up To 2000 GPM

Part No: Y4-M11A



Details

Manually Controlled Monitor - Up To 2000 GPM

Weight: 31.000 lbs (0.000 kg)

Monitor Configuration	Fixed Mount
Flow Rate - Monitors	0-2000 gpm (0-7600 l/min)
Operation Energy Source	Manual
Monitor Inlet	3 Inch ANSI 150
Monitor Outlet	3.5 inch (89mm)
Horizontal Control	Handwheel (6 Inch, Injection Molded Nylon)
Horizontal Movement (degrees)	Continuous 360
Vertical Control	Handwheel (6 Inch, Injection Molded Nylon)
Vertical Movement (degrees)	45 below to 90 above horizontal
Safety Shutoff	No Safety Shutoff
Pressure Relief Valve	No PRV
Valve Design	No Valve
Finish	Powdercoated Stardust Silver
Certifications	FM

Related Videos

- [Monsoon Monitor](#)

Online Technical Support Material

- [Y4-M11A](#)
- [Monsoon FM Approval](#)
- [4.5" Quick Connect Inlets for Elbows and Monitors](#)
- [Monsoon CCCF Certification](#)
- [Monsoon Monitor Instruction Manual](#)

PRODUCT SERIES OVERVIEW

• TFT Monsoon Manual Monitor offers efficient flow performance up to 2000gpm with only 15psi loss, provides full 360 degree rotational movement, and is available with 3" or 4" ANSI 150 flanges, 3" or 4" NPT thread, or with extended flange inlets to eliminate rotational clearance issues. All models are FM approved, are standard with corrosion resistant powder coating, and come with your choice of hand wheel and tiller bar operational controls.

• TFT Monsoon Remote Control Monitors are designed for operational pressures up to 200psi, provide up to 450 degrees of rotational travel, and have an elevation range of 90 degrees above horizontal to 45 degrees below. All Monsoon pumper and aerial RC monitor versions come standard with TFT's rugged electronics design which eliminates corrosion issues caused by water migration to electronic circuitry, have been awarded CE approval, and are easily controlled by panel mounted, tethered, or radio frequency operational controls.

• TFT Monsoon ATEX certified RC Monitors are designed for 12/24volt operations and are tested and approved for use in Classified Hazardous Locations as defined by European Directive 94/9/EC often referred to as the ATEX directive. This directive also indicates that the monitor and nozzles are suitable for Zone 2, Category 3 environments, use position encoding and current limiting for drive train protection, and have an IP65 rating for all electrical components.