



# Sho Flow

Portable electronic flow indicator for hand-held nozzle

## Shows your flow at a glance

### • Models :

4 flow ranges are possible :

- 100 – 475 l/min - Réf I13.30.025
- 175 – 750 l/min - Réf I13.30.026
- 250 – 1100 l/min - Réf I13.30.027
- 500 - 2000 l/min

### • Characteristics :

- 0,5 bar non-recoverable pressure loss at maximum flow
- Weight : 1 kg (2kg for 2000 l/min version)
- Dimensions : L.15 x W. 9 x D.8 cm (20 x 12 x 10 cm for 2000 l/min version)
- Quality 6061-T6511 aluminium hardcoat anodized body for corrosion protection
- Maximum operating pressure: 17 bar / Minimum operating pressure: 0.7 bar
- Measurement accuracy :
  - Pressure  $\pm 5\%$  full Scale ( $\pm 0.85$  bar)
  - Waterflow  $\pm 5\%$  full Scale ( $\pm 23$ ,  $\pm 38$  or  $\pm 55$  l/min)
- Temperatures :
  - Operating temperature: 0° to 70°C
  - Storage temperature: -35°to +85°C



- Warning alarm for flows below and above those selected
- Alternative pressure and flow display (only one display at a time is possible)
- Automatic stand-by setting after one minute operation if pressure falls below 0.7 bar



**LEADER**  
Tomorrow's technology today

ZF01.013.EN.1

As it is our policy to seek constant improvement of our products, we reserve the right to modify the specifications of our equipment without notice.