



B-BGH

Task Force Tips © 2013

ULTIMATIC W/GRIP 1" NH (25mm)

Part No: **B-BGH**



Details

ULTIMATIC W/GRIP 1" NH (25mm)
Full automatic 100 psi (7 bar) nozzle for use on 3/4" (19mm) or 1" (25mm) hose. Flow range of 10-125 gpm (40-500 l/min). Includes pistol grip mounted below the valve, flush without shutting down, six position detent flow control slide valve, "Gasket Grabber" inlet screen, and molded rubber bumper with "power fog" teeth. Lightweight hardcoat anodized aluminum for maximum resistance to corrosion and wear. 1" NH (25mm) full-time swivel is standard.

Weight: 3.400 lbs (1.542 kg)

Fog Pattern Method	Molded Rubber Teeth (fixed)
Flow Control Method	Automatic (constant pressure, variable flow, constant gallonage, flow does not change with pattern)
Flow Rate	10-125 gpm (40-500 l/min)
Coupling Size (Nozzles)	1.0 inch (25mm)
Coupling Style (Nozzles)	Knurled (Diamond pattern)
Coupling Swiveling/Rigid (Nozzles)	Swivel (full time, even after tightening)
Pressure	100 psi (7bar)
Nozzle Body Style	Nozzle with shutoff and pistol grip
Valve Design	Slide Valve (Stainless)
Valve Actuation Method	Horseshoe (Injection Molded Nylon w/ Colored Handle)
Nozzle Bumper Material	Rubber - bonded

Related Videos

- [Pistol Grip Replacement](#)
- [How to Adjust a TFT Slide Valve](#)
- [Ultimatic Series](#)
- [Visual Nozzle Inspection](#)

Online Technical Support Material

- [B-BGH](#)
- [Ultimatic 125 Automatic Nozzles \(Russian\)](#)
- [Service Poster - Ultimatic 125 Nozzles](#)
- [Using Automatic Nozzles w/ Foam Eductors](#)
- [Handheld Automatic Nozzle Instructions](#)
- [Ultimatic Flow Chart](#)
- [Folding Pistol Grip Installation](#)
- [Ultimatic ER Monitor Nozzles](#)
- [Field Lubrication Procedure](#)

PRODUCT SERIES OVERVIEW

• The Ultimatic nozzle incorporates TFT's unique stainless steel slide valve for turbulence free flow control and includes the exclusive integrated debris screen to prevent stream quality degradation. All models accept low and multi-expansion foam attachments for increased finished foam performance.

• The Ultimatic nozzle is available with 100 or 75 psi operational pressure choices to meet any fire ground operational challenge. The high strength bonded rubber fog teeth provide a full filled pattern that pushes heat flame and smoke ahead and away from the firefighting team.

• The Ultimatic nozzle comes standard with reflective labeling as well as your choice of color coded pistol grip and shut off handle. This constant pressure variable gallonage nozzle series is available in tip only and shut off configurations, is individually serialized, and comes with TFT's exclusive 5 year warranty.